

ARMY RESEARCH LABORATORY



Feasibility of the MUSIC Algorithm for the Active Protection System

Canh Ly

ARL-MR-501

March 2001

Approved for public release; distribution unlimited.

20010405 050

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Adelphi, MD 20783-1197

ARL-MR-501

March 2001

Feasibility of the MUSIC Algorithm for the Active Protection System

Canh Ly

Sensors and Electron Devices Directorate

Approved for public release; distribution unlimited.

Abstract

This report compares the accuracy of the doppler frequency of an incoming projectile with the use of the MUSIC (multiple signal classification) algorithm to the use of the fast Fourier transform (FFT) when applied to an active protection system (APS). Two simulated files and one measured data file were evaluated. The processing time with the MATLAB[®] software for the FFT is on the order of milliseconds, while for the MUSIC algorithm, it is on the order of seconds with similar accuracy. Therefore, the FFT is recommended for the application to an APS within the specified accuracy.

Contents

1. Introduction	1
2. Simulation Results	1
3. Conclusions	7
Distribution	9
Report Documentation Page	11

Figures

1. Simulated response for X1 data at 30-dB SNR	2
2. Simulated response for X3 data at 10-dB SNR	2
3. Measured response for F16dec.dat	3
4. Power spectral density for X1 data at 30-dB SNR	3
5. Power spectral density for X3 data at 10-dB SNR	4
6. Power spectral density for F16dec.dat	4
7. MUSIC result for X1 data at 30-dB SNR	5
8. MUSIC result for X3 data at 10-dB SNR	5
9. MUSIC result for F16dec.dat	6

Table

1. Comparison of FFT and MUSIC algorithm.	6
--	---

1. Introduction

An active protection system (APS) requires accurate knowledge of the doppler frequency of an incoming projectile. In this report, I consider two methods of computing the doppler frequency—the multiple signal classification (MUSIC)¹ algorithm and power spectral density (PSD) with the use of fast Fourier transform (1024-point FFT). Normally, MUSIC has been used to improve the resolution of multiple closely spaced targets. In this application, MUSIC is used to estimate accurately a single doppler frequency. In this report, I compared the results of the estimation of the doppler frequency of an assumed head-on projectile using PSD and the MUSIC algorithm; I wanted to determine whether the MUSIC algorithm performs better than PSD in terms of accuracy and processing time. These calculations were applied to three data files in this study. Each of these (X1 and X3) had 128 samples, which were synthesized and sampled at 33 ms. The X1 data were synthesized assuming a 30-dB signal-to-noise ratio (SNR), and the X3 data were synthesized assuming a 10-dB SNR. The third was a measured data set obtained in December 1998 called F16dec.dat. For more information about how these data were collected, please contact Wolfgang Wiebach at the Army Research Laboratory.² The data for this data file were sampled at 2 μ s. There were 625 samples.

2. Simulation Results

I ran the simulation for all three data files. All the calculations were computed by a Pentium II 400 MHz PC, with the use of MATLAB[®] software. Figures 1, 2, and 3 present the graphs of this data. Figures 4, 5, and 6 show the output of PSD with the use of FFT. In these figures, the peaks are the estimate of the doppler frequencies in kHz. Figures 7, 8, and 9 are the results of the MUSIC calculations. Again, the peaks from these MUSIC pseudospectra are the estimated doppler frequencies.

Table 1 shows the comparison of processing time and the estimated frequencies. We see that both FFT and the MUSIC algorithm give the same estimated doppler frequency within 0.1 percent. However, the MUSIC algorithm required much more processing time than the FFT calculations for all three data files.

¹Ralph O. Schmidt, "Multiple emitter location and signal parameter estimation," *IEEE Trans. Antennas Propag.*, AP-34, No. 3 (March 1986), pp 276–280.

²Personal communication.

Figure 1. Simulated response for X1 data at 30-dB SNR.




Figure 2. Simulated response for X3 data at 10-dB SNR.




Figure 3. Measured response for F16dec.dat.




Figure 4. Power spectral density for X1 data at 30-dB SNR.




Figure 5. Power spectral density for X3 data at 10-dB SNR.




Figure 6. Power spectral density for F16dec.dat.




Figure 7. MUSIC
result for X1 data at
30-dB SNR.




Figure 8. MUSIC
result for X3 data at
10-dB SNR.




Figure 9. MUSIC
result for F16dec.dat.




Table 1. Comparison
of FFT and MUSIC
algorithm.

Data file	FFT		MUSIC	
	Doppler frequency (kHz)	Time for calculation (s)	Doppler frequency (kHz)	Time for calculation (s)
X1	109.20	0.011	109.3	1.121
X3	110.09	0.012	110.0	1.152
F16dec.dat	102.54	0.011	102.5	43.79

3. Conclusions

I have shown the accuracy of the estimation of doppler frequency and the processing time for the APS with the use of PSD with 1024-point FFT and the MUSIC algorithm. The accuracy of doppler frequency estimates with the use of both PSD and MUSIC is within 0.1 percent of each other. However, with the requirement of an APS (fast speed and short processing time), I would recommend the use of PSD for this application rather than its counterpart.

Distribution

Admnstr
Defns Techl Info Ctr
ATTN DTIC-OCF
8725 John J Kingman Rd Ste 0944
FT Belvoir VA 22060-6218

DARPA
ATTN S Welby
3701 N Fairfax Dr
Arlington VA 22203-1714

Ofc of the Secy of Defns
ATTN ODDRE (R&AT)
The Pentagon
Washington DC 20301-3080

Ofc of the Secy of Defns
ATTN OUSD(A&T)/ODDR&E(R) R J Trew
3080 Defense Pentagon
Washington DC 20301-7100

AMCOM MRDEC
ATTN AMSMI-RD W C McCorkle
Redstone Arsenal AL 35898-5240

US Army TRADOC
Battle Lab Integration & Techl Dirctr
ATTN ATCD-B
FT Monroe VA 23651-5850

Dir for MANPRINT
Ofc of the Deputy Chief of Staff for Prsnl
ATTN J Hiller
The Pentagon Rm 2C733
Washington DC 20301-0300

SMC/CZA
2435 Vela Way Ste 1613
El Segundo CA 90245-5500

US Army ARDEC
ATTN AMSTA-AR-TD
Bldg 1
Picatinny Arsenal NJ 07806-5000

US Army Avn & Mis Cmnd
ATTN AMSAM-RD M Schexneider
ATTN AMSAM-RD W Caraway
Redstone Arsenal AL 35898

US Army CECOM NVESD
ATTN AMSEL-RD-NV-RSPO A Tarbell
Mailstop 1112
FT Monmouth NJ 07703-5000

US Army Info Sys Engrg Cmnd
ATTN AMSEL-IE-TD F Jenia
FT Huachuca AZ 85613-5300

US Army Natick RDEC Acting Techl Dir
ATTN SBCN-T P Brandler
Natick MA 01760-5002

US Army Simulation Train & Instrmntn
Cmnd
ATTN AMSTI-CG M Macedonia
ATTN J Stahl
12350 Research Parkway
Orlando FL 32826-3726

US Army TACOM
ATTN AMSTA-TR-R (Ms 263) J Soltesz
ATTN AMSTA-TR-M J Lim
Warren MI 48397-5000

Nav Surfc Warfare Ctr
ATTN Code B07 J Pennella
17320 Dahlgren Rd Bldg 1470 Rm 1101
Dahlgren VA 22448-5100

US Army Rsrch Lab
ATTN AMSRL-SE-RM S Stratton
ATTN AMSRL-WM-TA B Zoltoski
ATTN AMSRL-WM-TE A Niiler
ATTN AMSRL-WM-TE G Thompson
Aberdeen Proving Ground MD 21005

Director
US Army Rsrch Lab
ATTN AMSRL-RO-D JCI Chang
PO Box 12211
Research Triangle Park NC 27709

US Army Rsrch Lab
ATTN AMSRL-DD J M Miller
ATTN AMSRL-CI-AI-R Mail & Records
Mgmt
ATTN AMSRL-CI-AP Techl Pub (2 copies)
ATTN AMSRL-CI-LL Techl Lib (2 copies)

Distribution (cont'd)

US Army Rsrch Lab (cont'd)

ATTN AMSRL-SE-R B Wallace

ATTN AMSRL-SE-RM C Ly (5 copies)

ATTN AMSRL-SE-RM D W Vance

ATTN AMSRL-SE-RM E Burke

ATTN AMSRL-SE-RM G Goldman

ATTN AMSRL-SE-RM H Dropkin

ATTN AMSRL-SE-RM J Nemerich

ATTN AMSRL-SE-RM K Tom

ATTN AMSRL-SE-RM R Harris

ATTN AMSRL-SE-RM R Wellman

ATTN AMSRL-SE-RM W Wiebach

Adelphi MD 20783-1197

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE March 2001		3. REPORT TYPE AND DATES COVERED Final, Sept to Oct 2000
4. TITLE AND SUBTITLE Feasibility of the MUSIC Algorithm for the Active Protection System			5. FUNDING NUMBERS DA PR: AH44 PE: 61102A	
6. AUTHOR(S) Canh Ly				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Attn: AMSRL-SE-RM email: ly@arl.army.mil 2800 Powder Mill Road Adelphi, MD 20783-1197			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-MR-501	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory 2800 Powder Mill Road Adelphi, MD 20783-1197			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES ARL PR: ONE3HH AMS code: 611102.H44				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This report compares the accuracy of the doppler frequency of an incoming projectile with the use of the MUSIC (multiple signal classification) algorithm to the use of the fast Fourier transform (FFT) when applied to an active protection system (APS). Two simulated files and one measured data file were evaluated. The processing time with the MATLAB [®] software for the FFT is on the order of milliseconds, while for the MUSIC algorithm, it is on the order of seconds with similar accuracy. Therefore, the FFT is recommended for the application to an APS within the specified accuracy.				
14. SUBJECT TERMS power spectral density, doppler frequency, projectile			15. NUMBER OF PAGES 14	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	